

Mondrian® Plus 60 Slab



Do not use vibrating plate


1 bag of sand covers approx. 57 ft²

Pedestrian - Designed to withstand pedestrian traffic


Mondrian® Plus 60 Slab

	DIMENSIONS (MM)	DIMENSIONS (IN)	CODES	COLOURS	TYPICAL ROW
	A 60 x 165 x 330	2 3/8 x 6 1/2 x 13	PRESTIGE COLOURS		
	B 60 x 330 x 330	2 3/8 x 13 x 13	12052893	Range Margaux Beige	
	C 60 x 330 x 495	2 3/8 x 13 x 19 1/2	12052894	Range Amboise Beige	
Weight/unit (avg.)	14 kg	30 lb	12052566	Range Scandina Grey	
Surface/unit	0.11 m ²	1.17 ft ²	STANDARD COLOURS		
Area/layer	0.98 m ²	10.55 ft ²	12052891	Range Norvick Grey	
Area/cube	11.76 m²	12 Rows	126.60 ft²	12052892	Range Newport Grey
Qty/cube	A = 48	B = 48	C = 24	Sold in full cubes only	
Weight/cube	1666 kg	3667 lb	Production location Bolton		


LAYING PATTERNS



Linear
100% Mix A, B, C



Modular
100% Mix A, B, C



Modular
100% Mix A, B, C

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Mondrian Plus 60 Slab	CSA A231.1	±4.5 MPa	N/A	225 g/m ² after 28 cycles 500 g/m ² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

* Concave or convex warpage in one dimension: up to and including 450 mm: 2.0 mm / over 450 mm: 3.00 mm

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.