


Melville® 80 Small Rectangle Paver



Techniseal 1 bag of sand covers approx. 77 ft²

Pedestrian - Designed to withstand pedestrian traffic

Vehicular - Designed to withstand car traffic


Melville® 80 Small Rectangle Paver




	DIMENSIONS (MM)	DIMENSIONS (IN)
	80 x 190 x 380	3 1/8 x 7 1/2 x 15
Weight/unit	14 kg	30 lb
Unit/surface	13.89 unit/m ²	1.29 unit/ft ²
Area/layer	0.87 m ²	9.33 ft ²
Area/cube	7.83 m²	9 Rows
Length/row Soldier	2.28 lin. m	7.48 lin. ft
Length/cube Soldier	20.52 lin. m	67.34 lin. ft
Qty/cube	108 units	108 units
Weight/cube	1465 kg	3225 lb

CODES	COLOURS
PRESTIGE COLOURS	
10550871	Range Amber Beige (2)
10551033	Rockland Black (2)
10551031	Range Scandina Grey (1)
STANDARD COLOUR	
10550870	Range Shaded Grey (2)
Sold in full cubes only	
Production locations:	
(1) Cambridge	
(2) Québec	


TYPICAL ROW



LAYING PATTERNS



Linear



Herringbone

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Melville 80 Small Rectangle Paver	CSA A231.2	N/A	μ 50 MPa ≥ 45 MPa	225 g/m ² after 28 cycles 500 g/m ² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Joint sand compaction: Cover vibrating plate with a removable rubber tread (neoprene or polypropylene).

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.